

Drive Customer Satisfaction, Volume and Revenue Meet Ryko's newest car wash system: the SoftGloss Drive-Thru. Featuring the low-maintenance, high-quality equipment you've come to expect from Ryko, the SoftGloss Drive-Thru is perfect for automotive dealers, fleets and rental agencies. Its consistently clean results and high throughput will attract new customers to your business and provide a value-added service that will enhance customer satisfaction and increase service business.



FEATURES AND BENEFITS

Providing a freshly washed car is an easy and cost-effective way to improve customers' satisfaction and your company's sales and customer retention rate—and it's a painless process with the SoftGloss Drive-Thru. Installing the Drive-Thru is quick and easy, with minimal downtime. The system's small footprint minimizes the space needed to add a car wash, and the plumbing and electrical requirements are simple.

- Increased customer satisfaction and return business
- Minimal space requirements
- Simple plumbing and electrical for easy installation
- Excellent wash consistency
- Reduced labor and prep costs for a lower bottom line
- High throughput performance
- Rugged, low-maintenance equipment
- Available in drive-through or drive-in/back-out configurations

- Wraparound and top-brush combo combines top and side brushes for maximum cleaning power for vehicle front, sides, rear and top
- Arches provide precise and thorough chemical application and rinsing
- Guide rails provide easy and accurate vehicle navigation
- Wash control center integrates all wash components into one easy-to-use control unit
- Tech 21 blower—includes flash dry (optional)
 - Rocker panel brush (optional)
 - . . .

SPECIFICATIONS

	3-Brush Wet Wash	3-Brush Dry Wash	5-Brush Wet Wash	5-Brush Dry Wash
Tunnel Length	29'	39'	39'	49'
Tunnel Width	15'5"	15'5"	15'5"	15'5"
Tunnel Height	12'	12'	12'	12'
Electrical Requirements	3 electric motors (0.55 KW, 3 phase, 208/460V, 60HZ) and three variable-frequency drives (1 HP, 3 phase, 208V, 230V, 60 HZ)	3 electric motors (0.55 KW, 3 phase, 208/460V, 60HZ) and three variable-frequency drives (1 HP, 3 phase, 208V, 230V, 60 HZ)	5 electric motors (0.55 KW, 3 phase, 208/460V, 60HZ) and five variable-frequency drives (0.75 KW, 3 phase, 230/460V, 60HZ)	5 electric motors (0.55 KW, 3 phase, 208/460V, 60HZ) and five variable-frequency drives (0.75 KW, 3 phase, 230/460V, 60HZ)
Recommended Water Supply	18 GPM, 50 PSI, 1" water line to water manifold	18 GPM, 50 PSI, 1" water line to water manifold	23 GPM, 50 PSI, 1" water line to water manifold	23 GPM, 50 PSI, 1" water line to water manifold
Air Requirements	90 PSI, 3/8" line, 2 CFM	90 PSI, 3/8" line, 2 CFM	90 PSI, 3/8" line, 2 CFM	90 PSI, 3/8" line, 2 CFM
Blower	N/A	Three 10 HP dryers, 230/460V, 60HZ	N/A	Three 10 HP dryers, 230/460V, 60HZ









Only Ryko Can Offer All of This!

The most comprehensive line of car wash equipment solutions in the industry, with touch, touchless and tunnel options.













CleanTouch leads the industry in uptime with the only coast-to-coast, direct support program with locally based technicians and a full line of wash solutions. It all adds up to increased wash counts and higher profit margins.

- Equipment and Installation
- On-Site Service
- Preventive Maintenance
- CleanTouch Wash Solutions
 Remote Monitoring
- Online Tech Resources
- Central Dispatch
- Centralized Billing



Ryko Solutions, Inc. • 1500 SE 37th Street, Grimes, IA 50111 • (800) 284-7956 • www.ryko.com