



# JHE JASJO CLEAR

The SoftGloss Drive-Thru is built to last with high-quality parts and lowmaintenance. Perfect for automotive dealers, fleets and rental agencies. Its consistently clean results and high throughput will attract new customers to your business and provide a value-added service that will enhance customer satisfaction and increase service business.

. . . . . . . . .

#### FEATURES & BENEFITS

- + Minimal space requirements
- + Simple plumbing and electrical for easy installation
- + Reduced labor and prep costs for a lower bottom line
- + High throughput performance
- + Rugged & low-maintenance
- Available in drive-through or drive-in/back-out configurations
- + Wash up to 50 cars per hour
- Wraparound and top-brush combo provide for maximum cleaning power on all sides

- Arches provide precise and thorough chemical application and rinsing
- + Guide rails provide easy and accurate vehicle navigation
- + Wash control center integrates all wash components into one easy-to-use control unit
- + Tech 21 blower includes flash dry (optional)
- + Rocker panel brush (optional)



### SOFTGLOSS DRIVE-THRU

#### SPECIFICATIONS

	3-Brush Wet Wash	3-Brush Dry Wash	5-Brush Wet Wash	5-Brush Dry Wash
Tunnel Length	29'	39'	39'	49'
Tunnel Width	15'5"	15'5"	15'5"	15'5"
Tunnel Height	12'	12'	12'	12'
Electrical Requirements	3 electric motors (0.55 KW, 3 phase, 208/460V, 60HZ) and three variable-frequency drives (1 HP, 3 phase, 208V, 230V, 60 HZ)	3 electric motors (0.55 KW, 3 phase, 208/460V, 60HZ) and three variable-frequency drives (1 HP, 3 phase, 208V, 230V, 60 HZ)	5 electric motors (0.55 KW, 3 phase, 208/460V, 60HZ) and five variable-frequency drives (0.75 KW, 3 phase, 230/460V, 60HZ)	5 electric motors (0.55 KW, 3 phase, 208/460V, 60HZ) and five variable-frequency drives (0.75 KW, 3 phase, 230/460V, 60HZ)
Recommended Water Supply	18 GPM, 50 PSI, 1" water line to water manifold	18 GPM, 50 PSI, 1" water line to water manifold	23 GPM, 50 PSI, 1" water line to water manifold	23 GPM, 50 PSI, 1" water line to water manifold
Air Requirements	90 PSI, 3/8" line, 2 CFM	90 PSI, 3/8" line, 2 CFM	90 PSI, 3/8" line, 2 CFM	90 PSI, 3/8" line, 2 CFM
Blower	N/A	Three 10 HP dryers, 230/460V, 60HZ	N/A	Three 10 HP dryers, 230/460V, 60HZ









Providing a freshly washed car is an easy and cost-effective way to improve customers' satisfaction and your company's sales and customer retention rate—and it's a hassle-free process with the SoftGloss Drive-Thru. Installing the Drive-Thru is quick and easy, with minimal downtime. Our Drive-Thru's small footprint minimizes the space needed to add a car wash, making this the perfect addition to your location!

## PARTNER WITH THE BEST BRANDS













National Carwash Solutions | 1500 SE 37th Street, Grimes, IA 50111 | (800) 284-7956 | NCSWASH.com NCS reserves the right to revise designs, make corrections, add or delete features and change specifications at any time without notice or obligation.